

Aqua-Add Defoam

9045


Defoaming solutions for water-based furniture paints and varnishes **for industrial use.**

PRODUCT DESCRIPTION

General

Special solutions for water-based furniture paints and varnishes to reduce the formation of bubbles in pump and circulation systems; improves de-aeration during the initial drying phase.

Application area



Additive for water-based coatings for furniture and interior finishing.

Aqua-Add Defoam (904590600): wide range of uses, especially for airless application

Aqua-Add Defoam CC (9045106731): for use with curtain coating machines

PROCESSING

Processing instructions



- Please shake / stir the product before use.
- The temperature of the product and object, and the room temperature must be at least + 15 °C.
- Mix Aqua-Add Defoam (9045) carefully into the paint/varnish while stirring continuously.
- Slight thinning effect in the coating material after addition.
- Adding Aqua-Add Defoam (9045) can lead to pinholing. Compatibility with the coating system you are using needs to be tested.
- The drying behaviour of the coating system is not affected by the addition of Aqua-Add Defoam (9045).
- Paints/varnishes that have been mixed can be used as explained in the relevant technical data sheet.
- Any change in the processing sequence, environmental conditions, non-observance of instructions or the use of products not listed may have an unfavourable effect on the result.
- Please follow our **ARL 150 - Working guidelines for water-based furniture coatings.**

Quantity to be added



Quantity to be added: up to a maximum of 2%.

The quantity to be added will vary according to the area of use and equipment used.

Therefore please contact your sales representative.

Cleaning the working equipment

With water immediately after use.

**ORDERING INFORMATION****Size of trading unit**


11, 51

Product variants

Aqua-Add Defoam (9045090600)
Aqua-Add Defoam CC (9045106731)

FURTHER DETAILS**Durability / storage**

Min. 1 year(s) in the original sealed containers.



Make sure the product is protected against moisture, direct sunlight, frost and high temperatures (above 30 °C).

Safety information

The product is only suitable for industrial use.



Further information on the subject of safety during transport, storage and handling as well as disposal can be found in the relevant safety data sheet. The current version can be accessed on the Internet at www.adler-lacke.com.