

ADLER Aquafix Kupfer

8135 000300

Copper powder for real metal effects for industrial and professional use

	PRODUCT DESCRIPTION
General	Copper powder to achieve real metal effects on surfaces made of wood-based materials
Application area	• For the coating of furniture and interior finishing exposed to normal levels of stress, such as tabletops and shelves in the home, fronts and permanently visible areas, surfaces used on seating furniture and not permanently visible areas: Application areas III – IV in accordance with ÖNORM A 1610-12.
	Application in combination with a suitable topcoat system.
	PROCESSING
Instructions for use	• Carefully incorporate ADLER Aquafix Kupfer 8135 000300 into the paint/hardener mixture by stirring without forming lumps. Stirring is best done by machine using a basket agitator.
Quantity to be added	250 parts by weight to 105 parts by weight of paint or paint/hardener mixture
Cleaning the working equipment	With water immediately after use.
	To remove dried paint residues we recommend using ADLER Aqua- Cleaner 80080 (diluted 1:1 with water).
	ORDERING INFORMATION
Size of trading unit	1 kg

02-17 ZKL 8135

ADLER-Werk Lackfabrik, A-6130 Schwaz Tel: 0043/5242/6922-301, Fax: 0043/5242/6922-309, Mail: <u>technical-support@adler-lacke.com</u>

Our instructions for use are based on knowledge available currently and shall guide the purchaser / user to the best of one's knowledge, but, however, must be clarified for the areas of application and processing conditions on a case-to-case basis. The purchaser / user decides about the acceptance and use of the delivered product at his / her own risk, which is why we recommend that a sample piece be prepared to check the acceptability of the product. Our general terms and conditions of sale are otherwise applicable. All previous data sheets are rendered invalid with the issue of this one. Rights reserved for the modification of the container sizes, color shades and degrees of gloss available.

FURTHER DETAILS Durability/storage At least 1 year in the original sealed containers. Immediately seal the container to prevent humidity from • penetrating. Make sure the product is protected against moisture, direct sunlight, frost and high temperatures (above 30 °C). Do not store together with oxygen-rich and flammable • materials. Do not store together with substances liable to spontaneous • combustion. Keep away from oxidizing agents, as well as highly alkaline and • highly acidic materials. Please pay attention to the associated safety data sheet. The current version can be accessed on the Internet at www.adler-lacke.com. Keep away from heat, hot surfaces, sparks, open flames and other sources of ignition. Do not smoke. Formation of explosive / highly flammable dust/air mixtures • possible during use. Earth containers and equipment being filled.

- Use explosion-proof electrical equipment. •
- In case of fire: Use special powder for metal fires or carbon • dioxide (CO₂). Do not use water.

It is recommended to use safety gloves and safety glasses while processing.

The product is only suitable for industrial and professional use.

Safety-related information

