

Mattierungsmittel

8163

Matting agent in paste form for Pigmolux DC for use in industry and trade

PRODUCT DESCRIPTION

Product numbers


8163090147

General

Matting agent in paste form for water-based coating systems such as Pigmolux DC (3405) for creating hard-wearing, matt surfaces in all interior finishing settings.

Application area

Matting agent in paste form for water-based furniture paints and varnishes.



PROCESSING

Processing instructions




- Please stir and shake the product well before use.
- The temperature of the product and object, and the room temperature must be at least + 15 °C.
- Carefully stir the Mattierungsmittel (8163) into the unhardened and undiluted paint/varnish; then stir in the hardener and the required quantity of thinner.
- Mattierungsmittel (8163) will result in a noticeable reduction in the degree of gloss of the original paint/varnish – depending on the amount used.
- The drying behaviour of the coating system is not affected by the addition of Mattierungsmittel (8163).
- Mixed paints and stains must be processed as specified in the corresponding technical data sheet.
- Any change in the processing sequence, environmental conditions, non-observance of instructions or the use of products not listed may have an unfavourable effect on the result.
- Please follow our **ARL 150 - Working guidelines for water-based furniture coatings**.

Quantity to be added



Max. 4 - 5 % by weight of the paint/varnish.

The quantity to be added will vary according to the area of use and equipment used. Therefore please contact your sales representative.

Cleaning the working equipment

With water immediately after use.

To remove dried paint residues we recommend using Aqua-Cleaner (8029) (diluted 1:1 with water).

ORDERING INFORMATION**Size of trading unit**

3 kg, 20 kg

FURTHER DETAILS**Durability / storage**

Min. 6 month(s) in the original sealed containers.

Make sure the product is protected against moisture, direct sunlight, frost and high temperatures (above 30 °C).

Close opened containers well and use up the content as soon as possible.

Safety information

The product is only suitable for the industrial and professional use.

Further information on the subject of safety during transport, storage and handling as well as disposal can be found in the relevant safety data sheet. The current version can be accessed on the Internet at www.adler-lacke.com.
