

Polyactive SB

8059

Cleaning and activation agent for use on PVC and coatable plastics for professional and industrial use

PRODUCT DESCRIPTION

Product numbers

805900021011

General

Solvent-based special cleaner for the pre-treatment of PVC and coatable plastics. Reliably removes contaminants, activates the surface and improves the adhesion of subsequent coatings. The product's yellow colour enables visual inspection of the treated surfaces and increases process reliability during pre-treatment.

Application area



Windows and front doors made of PVC and other synthetic material suitable for coating.

PROCESSING

Processing instructions



- Please stir and shake the product well before use.
- The temperature of the product and object, and the room temperature must be at least + 15 °C.
- The optimal conditions for use are between 15 - 25 °C with a relative atmospheric humidity between 40 - 80 %.
- Moisten a clean cloth with Polyactive SB (8059) and wipe the surface to be coated with moderate pressure.
- Wisch- und Poliертuch (9662) is recommended for application.
- The cloth should be changed after about 20 linear meters.
- Recoating must take place within 10 to 60 minutes.
- Any change in the processing sequence, environmental conditions, non-observance of instructions or the use of products not listed may have an unfavourable effect on the result.

SUBSTRATE

Type of substrate

PVC and coatable plastics

ORDERING INFORMATION

Size of trading unit	11
Supplementary products	Wisch- und Poliertuch (9662)

FURTHER DETAILS

Durability / storage	Min. 1 year(s) in the original sealed containers.
-----------------------------	---

Safety information

The product is only suitable for the industrial and professional use.
Further information on the subject of safety during transport, storage and handling as well as disposal can be found in the relevant safety data sheet. The current version can be accessed on the Internet at www.adler-lacke.com.